

Technical Data Sheet

Issue date: 05/01/2005 Date last modification: 09/10/2014

VISCOM - Specialties

01351 RI-1960/50 PVC ULTRADESTRUCTIBLE MATT WHITE ASP WKPE144

Face Material

Ultradestructible white cast vinyl.

Type Cast vinyl Colour and Finish Matt white

Adhesive

Permanent adhesive with good initial tack with rapid bond built to ensure destructibility.

Reference ASP

Type Permanent acrylic

Min. Appl. Temp. -5°C

Service Temp. -10°C to +110°C

Shear Good

Tack Medium N/inch² Final Adhesion Very high N/inch

Liner

Type Siliconised two side PE Kraft

Colour and Finish White

Applications

Tamperproof labels that once applied has the characteristic of being ultra-destructible when tampered with, because the frontal face tears as pressure is applied.

Printing Methods

Printable in letterpress UV, screenprinting UV and thermal transfer.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

6 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50 \pm 5% of Relative Humidity.
- · Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.







