

PROFILINE



[SPECIALITIES] : SOLO Floor Easy

GENERAL INFORMATION

Monomeric PVC (embossed, transparent matt, 120 μ) with a clear solvent based acrylic adhesive (permanent), laminated on two-sided PE-coated silicone paper liner (150 gsm).

The PVC offers an excellent dimensional stability.

Especially designed for floorgraphic applications with anti-slippery character and scratch resistant surface for mid-term floor decoration and advertising (airports, railway stations, shopping centers).

RECOMMENDATIONS FOR LAMINATING

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

SHELF LIFE

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

SAFETY DATA SHEET

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

TECHNICAL DATA

Carrier:	monomeric PVC (embossed), highly stabilized, calendered
Thickness:	120 μ +/- 5 %
Adhesive:	clear solvent acrylic, permanent
Adhesion:	5,5 N/cm +/- 5%
Liner:	two-sided PE-coated silicone paper (150 g/m2)
Application temperature:	+10 - +40 °C
Service temperature:	- 20 - +50 °C
Outdoor durability:	3 years (For application as protection film) 6 months (For application as floorgraphic- film with anti-slippery character)

STANDART DIMENSIONS

1050 mm x 50 m
1370 mm x 50 m
1550 mm x 50 m

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of SOLO Media, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. SOLO Media makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.

MEDIA for [eco] SOLVENT-BASED