

VISCOM-DIGITAL - SOFT VINYL

Issue date : 15/01/2013
Date last modification : 03/06/2014

08198 HI-GRIP 75 POLY GLOSS WHITE ASP32 WK135
Face Material

Gloss white polymeric soft vinyl.

Type	Polymeric vinyl
Colour and Finish	Gloss white
Weight	100 g/m ² ±10% ISO-536
Thickness	75 µ ±10% ISO 534-80

Adhesive

Permanent adhesive with excellent adhesion on low energy surfaces (i.e. PP or PE containers). The adhesive has a very high peel adhesion and medium cohesion.

Reference	ASP32
Type	Permanent
Min. Appl. Temp.	+5°C
Service Temp.	-35°C / +70°C
Shear	Medium
Tack	13 N/25mm FINAT FTM9
Final Adhesion	15 N/25mm FINAT FTM2

Liner

Type	One side siliconised clay coated Kraft
Colour and Finish	White
Weight	135 g/m ² ±10% ISO 536
Thickness	145 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

Applications

Decorative applications for plastics fairing or tanks for motocross, quad bikes and Go Karts; Warning applications on heavy equipment and industrial trucks.

Printing Methods

Printable with UV and solvent screen-printing, UV offset and solvent and eco-solvent based ink-jet. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.