# TEXTILELINE



## [ART]: Vernon Grand Textile

### **GENERAL INFORMATION**

Polyester textile is onesided coated with a special polymer with high whiteness. Caused by the polymercoating you get in combination with solvent- UV- curable and HP- Latex- inks a highly brilliant print. It is characterised by a high flexibility, highest print quality, no white cracking, no creasing colours, trimming hot or cold without fraying, soft textile haptics.

#### RECOMMENDED APPLICATION

Indoor, Pop ups, Roll Ups, Banner, professional photography application, theare, movie, backdrops, wall covering, pictures

#### **SHELF LIFE**

2 years when stored in the original packaging between  $20^{\circ}\text{C}$  and  $25^{\circ}\text{C}$  at 50% relative humidity.

#### **TECHNICAL DATA**

Substrate: 100 % Polyester (PES) / DIN 60001 /

Weight:  $190 \pm 10 / DIN EN ISO 2286-2 /$ 

Thickness:  $\geq 0.35$  / DIN EN ISO 2286-3 /

Coating: with a special polymercoating

Tensile strength warp/weft:  $\geq$  80/40 daN/5cm / (DIN EN ISO 13934-1/

Tear resistance warp/weft:  $\geq$  15/18 N / (DIN EN ISO 13937-1/

Whiteness:  $\geq 100$ 

Type of ink: all solvent, eco-solvent, uv-curable and

HP Latex - inks

Use: Indoor / Outdoor

Flame Retardant: no

#### **SAFETY DATA SHEET**

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

#### **STANDART DIMENSIONS**

1370 mm x 30 m 1620 mm x 30 m

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is to the best knowledge and belief of SOLO Media, accurate and reliable, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. SOLO Media makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility.